

09999 424 8562660




Fig. 1
1/5

20

CYLINDER
DEPOSIT
REQUIRED

IF THIS SHRINK
WRAP IS REMOVED
A SERVICE CHARGE
WILL BE APPLIED !

REFRIGERANT

RECOVERY

FOR MSDS : WWW.POL

PHONE : 603-394-8041

CUSTOMER INFORMATION

NAME :

ADDRESS :

RETURNED BY :

PHONE :

CONTACT :

Fig 2B

Fig 20


2/5 Fig. 2 A

20

30



CYLINDER



CLARREFRIGERANT.COM

TEL - FAX : 603-394-8043

REFRIGERANT INFORMATION

- ☐ R-22 CHLORODIFLUOROMETHANE (UN-1018)
☐ R-12 DICHLORODIFLUOROMETHANE (UN-1028)
☐ R-134a 1,1,1,2 TETRAFLUOROETHANE (UN-1956)
☐ OTHER _____

TOTAL CYLINDER WEIGHT : _____

RETURN DATE : _____

22/40

Fig. 2a

Fig. 2c

3/5 Fig. 2B

20

T0927 8562660

<p>40</p> <p>FOR INTERNAL USE :</p> <p>REFRIGERANT :</p> <p>NET WEIGHT :</p> <p>TEST #</p>	<p>22</p>	<p>50</p> <p>FOR INTERNAL USE :</p> <p>CYLINDER CERTIFICATION :</p> <p>TECHNICIAN :</p>
--	-----------	---

REFRIGERANT SERVICES

BUY BACK OF ALL REFRIGERANTS FROM 50 - 50,000 LBS.

TESTING OIL & REFRIGERANTS

RENTAL RECOVERY EQUIPMENT

RECLAIM & RETURN OF YOUR REFRIGERANT

DOT CERTIFIED TO TEST ANY SIZE TANK

WASTE OIL REMOVAL

VIRGIN REFRIGERANT SALES, ANY TYPE, ANY SIZE, ANYTIME!




Fig 20

Fig 20

4/5 Fig 20

32 FIRST AID 30

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen. Avoid stimulants. Do not give adrenaline (epinephrine) call a physician. In case of contact, flush eyes promptly with plenty of water for at least 15 minutes. Call a physician. Flush exposed skin with water (not hot) or use other means to warm skin slowly.

34 ATTENTION - WHEN FULL 30

Liquid and gas under pressure. Vapor reduces oxygen available for breathing. Can cause rapid suffocation. Inhalation or misuse of product can result in serious personal injury or death. May decompose in contact with hot metal surfaces to release toxic, corrosive decomposition products. Contact of liquid with skin or eyes may cause irritation or frostbite. Overheating, pressurizing or rusting can cause cylinder to burst, resulting in serious personal injury or death.

MINIMUM PRECAUTIONARY MEASURES

- Do not inhale vapors.
- Store and use with adequate ventilation-never in a closed space.
- Avoid contact with eyes, skin and clothing.
- Do not store in direct sunlight or heat above 125°F (51°C)
- Do not store in damp areas
- Do not drop or subject this cylinder to rough handling
- Do not tamper with safety relief device or the valve
- Always properly evacuate recovery machine before changing refrigerants.
- SEE ADDITIONAL INFORMATION ON THE CYLINDER

WHOLESALE: 20

BRANCH: _____

AGENT: _____

P.O. #: _____

ADDITIONAL COSTS:

RETURN SAME CYLINDER ☐ YES / ☐ NO

IF YES, PROVIDE COMPLETE INFO

RETURN SENSOR ☐ YES / ☐ NO

UNDER FILLED ☐ YES / ☐ NO

OTHER _____

CAUTION

30

DO NOT FILL OVER 80%

REFRIGERANT MAY BE REJECTED OR
HANDLING CHARGES MAY BE APPLIED
IF REFRIGERANTS ARE MIXED OR
CONTAMINATED.

5/s Fig 20